

SMA "Silver" Series Manual Chain Hoist



1/2 – 5 metric ton Lifting Capacity

Features:

A NEW design for the year 2000 workplace with safety and performance in mind. Meets or exceeds world specifications including ASME B30.16. A value line product with premium features at a Great Price.

- Overload Protection to deter and reduce downtime and repair costs resulting from abuse.
- All steel, low headroom, light weight construction.
- Self-adjusting disc type double pawl mechanical load brake.
- Hardened roller bearings for maximum efficiency and durability.
- Improved 4 layer finish of nickel, copper, nickel, and chrome complementing our Silver Series lever hoist companion product.
- Ideally suited for the Rental and Construction markets.
- Standard lift (L) is 10 feet, Hand chain drop (D) is 2 feet less than lift (unless specified).

Options:

- Bullard bottom hooks for single fall models only.



SMA Series Specifications

Model no.	Capacity		Pull to lift rated load lbs	Chain o'hauled to lift load 1 ft	Net wt of chain per ft of lift lbs	No. of chain falls	Load chain size mm	Ship wt w/10 ft of lift lbs
	metric tons	lbs						
SMA005	1/2	1100	48	25	.55	1	6.3 x 18	18
SMA010	1	2200	75	39	.55	1	6.3 x 18	26
SMA015	1 1/2	3300	84	58	.80	1	8.0 x 24	39
SMA020	2	4400	81	75	1.10	2	6.3 x 19	35
SMA030	3	6600	90	116	1.60	2	8.0 x 24	55
SMA050	5	11000	97	187	1.40	2	10.0 x 30	86

Note:
Standard lift 10

SMA Series dimensions (in.)

Model	A (min)	B	C	D	E	F	G	J
SMA005	11.6	5.3	.82	.85	.60	2.8	4.2	.59
SMA010	13.0	5.7	1.0	1.1	.78	3.6	5.1	.75
SMA015	16.1	7.6	1.1	1.2	.97	4.1	5.8	.87
SMA020	17.7	5.7	1.2	1.3	1.1	4.5	5.1	.98
SMA030	20.7	7.6	1.4	1.5	1.4	5.1	5.8	1.1
SMA050	24.0	8.3	1.5	1.7	1.7	5.9	6.6	1.3

Note:
Dimensions are subject to change.

